


# TUNNEL SOFTWARE FEATURES



## MAIN FEATURES

4G 3G/2G	Serial to 2G/3G/4G	IN OUT	GPIO control	GPS	GPS management	Dyn DNS	DynDNS and No-IP
Internal web server		RF mesh concentrator		Intelligent relays		SMS	SMS to serial

### Connectivity

- 2G/3G/4G serial gateways: TCP client, TCP server, UDP client/server, accept incoming CSD calls, up to 2 simultaneous tunnel
- GPRS connectivity mode: permanent 100% time, under request (SMS, missed call), change on a digital input, analog input out of level, serial data on RS232/RS485 port, scheduled date/hour/time

### TCP Services

- Web server and Telnet
- Remote access by web browser
- Shows the status of digital and analog inputs
- Change digital output level and relays
- Execute AT commands remotely

### Security

- Authorized phone numbers
- Firewall IP
- SSL connections

### SMS Alarm and Control

- Send SMS alarm when the level of digital input change
- SMS can be sent to up to 10 remote users
- Execute remote AT commands
- Change the status of digital outputs & relays
- Alias method is allowed

### Solutions for Dynamic IP

- GPRS session using a SMS or missed call
- DynDNS and NoIP
- Private DNS

### Metering, Modbus, Sensors...

- 868 MHz remote monitoring sensors (Wavenis)
- Modbus RTU devices
- Relays control
- Access to serial devices using GPRS and GSM